



MPC-12/MPC-12C 12-Slot Universal Mini-Mod Chassis and Power Supply MPC-PSF12/16 Universal Power Supply Module

- High capacity fully regulated power supply provides the most efficient performance, ensuring reliability over a wide range of environmental conditions
- High efficiency power supply (over 70%) equipped with cooling fan minimizes power consumption and heat dissipation
- Current overload protection prevents damage to system and prolongs power supply life
- Internal fusing circuitry provides current overload protection and precise voltage regulation, preventing component damage

MPC-BP Universal-Chassis Blank Plate

- Blocks escape of cool air when used with forced air ventilation systems
- Provides uniform look when not all module slots are filled
- Slides easily into Pico Macom mini-chassis systems and those of other manufacturers

Specifications

Module Capacity	12	RF Output Conn.	75 F-Female
Input Voltage Range	90-240VAC	UR Listed Power Supply	Yes
Input Voltage Frequency	47~63Hz	Operating Temperature	10~50°C
Power Required	68 Watts Each	Dimensions	
Output Volt. (V1) @ 4A	5VDC	MPC-12/12C	19" (L) x 7.5" (D) x 3.5" (H)
Output Volt. (V2) @ 4A	12VDC	MPC-BP	1" (L) x 4" (D) x 3.4" (H)
Efficiency	70%	Weight	
Line Load Regulation	±1%	MPC-12	7.8 lbs.
Minimum Load	10%	MPC-BP	0.4 lbs
Video Input Conn.	75 F-Female		
Audio Input Conn.	5K F-Female Unbalance		

Ordering Information

MPC-12	12 Slot Universal Mini-Mod Chassis and Power Supply	MPC-BP	Universal-Chassis Blank Plate
MPC-12C	12 Slot Universal Mini-Mod Chassis Only	MPC-PSF12/16	Universal Power Supply